Open Horizon Scientific Review

Vol. 02 No.02 2024

Development of Bio-Based Solvents for Environmentally Responsible Chemical Manufacturing

Sana Iqbal Malik [1]

[1] Department of Chemical Engineering, NED University of Engineering and Technology, Karachi Pakistan

ABSTRACT

Solvents account for the largest share of mass used in many chemical manufacturing processes and are a major source of waste, energy consumption and emissions. Conventional petroleum-derived solvents such as hexane, dichloromethane, N,N-dimethylformamide and N-methyl-2-pyrrolidone raise serious concerns related to toxicity, volatility and regulatory restrictions. Bio-based solvents, derived from lignocellulosic biomass, sugars, vegetable oils and other renewable resources, offer a promising route to reduce environmental impact while maintaining process performance. This article reviews the principles that define a green solvent, the renewable feedstocks and production routes for bio-based solvents, and the main classes of these compounds, including alcohols, esters, ethers, lactones, terpenes and levoglucosenone-derived products. Their physical properties, performance in synthesis, extraction, coatings and pharmaceutical processes, life cycle environmental profiles and safety aspects are compared with those of conventional solvents. The main technical, economic and regulatory barriers to large-scale adoption are discussed, and research priorities for the development of truly sustainable solvent systems are outlined.

Key words : *bio-based solvents, green chemistry, renewable feedstocks, sustainable manufacturing, life cycle assessment*

Introduction:

Chemical manufacturing underpins modern life, supplying pharmaceuticals, polymers, agrochemicals, coatings, electronics and countless consumer products. Almost every one of these products is made with the help of solvents, which dissolve reactants, control reaction rates, transfer heat, separate products and clean equipment. In typical fine chemical and pharmaceutical processes, solvents can represent more than half of the total mass of materials used and a large proportion of the waste generated. The choice of solvent therefore has a major influence on the cost, safety and environmental footprint of a process.Historically, most industrial solvents have been produced from crude oil or natural gas. Many of them are volatile organic compounds that contribute to air pollution and photochemical smog, and several are toxic, carcinogenic or harmful to reproduction. Regulations such as the European REACH framework have restricted the use of substances including dichloromethane, N,N dimethylformamide and N-methyl-2-pyrrolidone, creating an urgent need for safer alternatives. At the same time, the growing awareness of climate change and the depletion of fossil resources has stimulated interest in replacing petrochemical raw materials with renewable carbon.Bio-based solvents are

compounds obtained wholly or partly from biomass through fermentation, chemical conversion or extraction. Ethanol from sugar fermentation, ethyl lactate from lactic acid, limonene from citrus peel and glycerol from biodiesel production are long-established examples, while newer products such as 2-methyltetrahydrofuran, gamma-valerolactone and dihydrolevoglucosenone are produced from lignocellulosic residues. It is important to note that a renewable origin does not automatically make a solvent green, because toxicity, energy demand in production and end-of-life behavior must also be considered.This article gives a structured overview of the development of bio-based solvents. It starts with the guiding principles and the available feedstocks, describes the major solvent classes and production methods, and compares their properties and performance with conventional solvents. It then examines applications, environmental assessment, safety and economics, and closes with the main challenges and future perspectives, followed by a brief summary.

Concept and Principles of Bio-Based Solvents:

The development of bio-based solvents is guided by the twelve principles of green chemistry, particularly the use of renewable feedstocks, the design of safer chemicals, the avoidance of auxiliary substances where possible and the design for degradation. A green solvent is expected to be derived from renewable resources, to have low toxicity and low environmental persistence, to be produced with low energy and waste, and to be easily recovered and recycled. No single solvent satisfies all of these criteria perfectly, so evaluation always involves a balance of several attributes.A bio-based solvent is defined by the origin of its carbon, which is measured as the percentage of biogenic carbon in the molecule and can be verified by radiocarbon analysis. This definition is independent of the molecular structure, and many bio-based solvents are chemically identical to petrochemical ones. Bioethanol and ethanol from ethylene are the same compound, but their carbon footprints differ. In other cases the solvent is a new molecule that can only be produced from biomass because of its oxygen-rich structure, which gives it distinctive polarity and hydrogen-bonding properties.Solvent selection guides developed by pharmaceutical companies and by international consortia rank solvents according to safety, health and environmental criteria, and they provide a practical framework for replacing hazardous materials. These guides place many bio-based solvents such as ethanol, ethyl acetate and ethyl lactate in the recommended category, while flagging others for further study. Their use encourages chemists and engineers to consider greener alternatives early in process design, when changes are easiest and cheapest to implement.

Feedstocks and Renewable Sources:

The renewable carbon for bio-based solvents is obtained from several categories of biomass. First-generation feedstocks include starch and sugar crops such as maize, sugarcane and sugar beet, which are fermented to ethanol, lactic acid and other products. Because these crops are also food sources, the use of non-food feedstocks is strongly preferred. Second-generation feedstocks consist of lignocellulosic residues such as wheat straw, rice husk, sugarcane bagasse, corn stover and wood waste, which contain cellulose, hemicellulose and lignin and are available in large quantities as

agricultural by-products.Vegetable oils and fats supply glycerol and fatty acid esters, and the rapid growth of the biodiesel industry has made glycerol a widely available and inexpensive platform chemical. Citrus peel and pine resin provide terpenes such as limonene and pinene through steam distillation and extraction, and waste cooking oil is increasingly used as a low-cost raw material. Marine biomass, including algae, and organic municipal wastes are being investigated as further sources of carbon for solvent production.For a country such as Pakistan, with a large agricultural sector, abundant residues from sugarcane, rice and wheat crops and a substantial sugar industry, the local production of bio-based solvents could offer both environmental and economic benefits. The use of residues avoids competition with food production, adds value to materials that are often burned in the field and reduces dependence on imported petrochemical solvents. However, the seasonal availability, dispersed collection and variable composition of such residues create logistical challenges that must be addressed in practical biorefinery design.

Major Classes of Bio-Based Solvents:

Alcohols were the first bio-based solvents to be used on a large scale. Ethanol, obtained by fermentation of sugars, and butanol, obtained by acetone-butanol-ethanol fermentation or catalytic upgrading of ethanol, serve as solvents in coatings, cleaning products, extractions and pharmaceutical formulations. Glycerol and its derivatives, including glycerol carbonate and solketal, are polar and low-volatility solvents with high boiling points and low toxicity, and they are used as green reaction media and as co-solvents.Esters and ethers form a second large group. Ethyl lactate, produced by esterification of fermentation-derived lactic acid with ethanol, is biodegradable, has low toxicity and dissolves a wide range of polar and non-polar solutes, making it a suitable replacement for halogenated solvents in cleaning and extraction. Ethyl acetate and butyl acetate can be produced from bio-ethanol and bio-butanol. Among ethers, 2-methyltetrahydrofuran, obtained by hydrogenation of furfural or levulinic acid, behaves like tetrahydrofuran but has limited miscibility with water and greater stability toward strong bases, which makes it attractive in organometallic chemistry and biphasic extractions.Lactones, terpenes and levoglucosenone derivatives complete the picture. Gamma-valerolactone, formed from levulinic acid by hydrogenation, is a stable polar aprotic liquid with low volatility that can replace dipolar aprotic solvents in some reactions. Dihydrolevoglucosenone, marketed under the name Cyrene, is produced in two steps from cellulose and is a promising substitute for N,N-dimethylformamide and N-methyl-2-pyrrolidone in amide coupling, cross-coupling and the preparation of membranes. Terpenes such as limonene, which is non-polar, serve as alternatives to hexane and toluene in extraction and degreasing, although their reactivity toward oxidation must be managed.

Production Routes and Catalytic Conversion:

Bio-based solvents are produced through three broad strategies. Direct extraction recovers compounds that already exist in biomass, as in the steam distillation of limonene from citrus peel. Fermentation uses microorganisms to convert sugars into alcohols, organic acids and diols, and it is the basis of ethanol, butanol and lactic acid production. Chemical catalytic conversion transforms biomass-derived

platform molecules into solvents through hydrolysis, dehydration, hydrogenation, esterification and related reactions, and it is the main route to furfural-derived and levulinic-acid-derived solvents.Platform molecules play a central role in these conversions. Acid-catalyzed hydrolysis and dehydration of hemicellulose pentoses gives furfural, and a similar treatment of hexoses gives 5-hydroxymethylfurfural and levulinic acid. Hydrogenation of furfural gives furfuryl alcohol and 2-methyltetrahydrofuran, while hydrogenation of levulinic acid gives gamma-valerolactone. Pyrolysis of cellulose in the presence of an acid catalyst yields levoglucosenone, which is hydrogenated to Cyrene. Glycerol is converted into solketal by reaction with acetone and into glycerol carbonate by reaction with dimethyl carbonate or urea.The efficiency of these routes depends heavily on catalyst design. Heterogeneous catalysts such as zeolites, sulfonated carbons, supported noble metals and base metal catalysts allow easy separation and reuse, and they are replacing corrosive mineral acids and homogeneous catalysts. Process intensification, including continuous flow reactors, reactive distillation and membrane separation, reduces energy use and improves yields. The integration of solvent production into biorefineries, in which fuel, chemicals and materials are co-produced from the same feedstock, is considered essential for achieving economically competitive costs.

Physicochemical Properties and Solvent Performance:

The suitability of a solvent for a particular process depends on its polarity, hydrogen-bonding ability, boiling point, viscosity, density, miscibility with water, stability and ability to dissolve specific solutes. Hansen solubility parameters, which describe dispersion, polar and hydrogen-bonding interactions, are commonly used to match solvents to solutes, and the solvatochromic parameters of Kamlet and Taft provide a complementary measure of polarity. Bio-based solvents typically contain oxygen atoms and therefore show higher polarity and hydrogen-bonding capacity than hydrocarbons, so they often serve as replacements for polar rather than non-polar petrochemical solvents.Boiling point is a practical parameter because it determines the volatility, the energy required for recovery and the temperature range of the reaction. Low-boiling solvents such as ethanol and 2-methyltetrahydrofuran are easy to remove by evaporation, whereas high-boiling solvents such as gamma-valerolactone and Cyrene are suited to reactions at elevated temperatures and generate fewer emissions but require more energy or alternative techniques for recovery. The graph below compares the boiling points of representative bio-based solvents and marks the boiling points of the conventional dipolar aprotic solvents they are intended to replace.

Applications in Chemical Manufacturing:

In organic synthesis and pharmaceutical manufacturing, bio-based solvents are used as reaction media, extraction solvents and crystallization solvents. 2-Methyltetrahydrofuran is widely used in Grignard reactions, lithiation and palladium-catalyzed couplings, in which it often improves yields and simplifies work-up because of its limited water miscibility. Cyrene and gamma-valerolactone have been successfully used in amide bond formation, Suzuki and Heck couplings and in the synthesis of metal-organic frameworks, showing that dipolar aprotic solvents can be

replaced without significant loss of efficiency in many cases.In extraction and separation, ethanol, limonene and ethyl lactate are used to obtain natural products such as essential oils, polyphenols, pigments and lipids from plant material. The replacement of hexane in vegetable oil extraction by 2-methyltetrahydrofuran or ethanol is a well-studied example. Bio-based solvents are also used in paints, inks, adhesives and cleaning formulations, where low toxicity, pleasant odor and good solvency for resins and greases are important advantages. In polymer chemistry, they serve as media for polymerization and as solvents for membrane casting, and glycerol-derived and sugar-derived solvents are used in the preparation of biocompatible materials.In the energy and materials sector, bio-based solvents are used in biomass pretreatment, in the formulation of electrolytes and in the dissolution of cellulose. Gamma-valerolactone has been shown to fractionate lignocellulose efficiently, and mixtures of bio-based solvents with water or with ionic and deep eutectic liquids can solubilize recalcitrant polymers. These applications show that bio-based solvents are not only substitutes for existing materials but also enable new, more sustainable processing concepts.

Life Cycle Assessment and Environmental Impact:

The environmental benefits of a bio-based solvent must be demonstrated by life cycle assessment, which accounts for all stages from feedstock cultivation to production, use and disposal. Typical impact categories are global warming potential, fossil resource depletion, acidification, eutrophication, land use, water use and human and ecosystem toxicity. Studies show that bio-based solvents often have lower fossil carbon footprints than their petrochemical equivalents, but this advantage is not automatic and depends on the feedstock, the energy source and the efficiency of the conversion process.Agricultural feedstocks introduce impacts such as fertilizer use, land transformation and water consumption that are absent in petrochemical routes, and these can offset or even exceed the savings in greenhouse gas emissions. Residue-based feedstocks generally give better results because they are by-products and carry only a small part of the upstream burden. The energy required for distillation, dehydration and purification is another major contributor, which explains why the improvement of separation efficiency and the use of renewable energy are so important.End-of-life behavior is a further consideration. Many bio-based solvents, such as ethanol, ethyl lactate and glycerol derivatives, are readily biodegradable and have low aquatic toxicity, but others, such as some terpenes, may be toxic to aquatic organisms. Since solvents are generally recovered by distillation and reused, the relevant environmental performance depends on the recovery rate and the energy needed for recycling as much as on the origin of the solvent. A fair assessment therefore compares the complete process, including solvent recovery, rather than the solvent alone.


Safety, Regulation and Economic Considerations:

Bio-based solvents can offer safety advantages such as higher flash points, lower volatility and lower toxicity than the substances they replace, but each compound must be evaluated individually. Some ethers, including 2-methyltetrahydrofuran, can form peroxides on storage and require stabilizers, and terpenes can cause skin sensitization. Newly introduced molecules such as Cyrene require

complete toxicological and ecotoxicological data in order to be registered and used on an industrial scale, and the cost of generating these data can slow commercialization.Regulatory frameworks are an important driver for the transition. Restrictions on dichloromethane, N,N-dimethylformamide, N-methyl-2-pyrrolidone and certain hydrocarbons in Europe and other regions, together with corporate sustainability commitments and bio-based product labeling schemes, create market demand for alternatives. Clear standards for the determination of bio-based carbon content and for the claims made about sustainability help prevent misleading marketing and allow purchasers to make informed choices.Economic competitiveness remains one of the main obstacles. Petrochemical solvents benefit from mature infrastructure, large production scale and low raw material costs, whereas many bio-based solvents are produced in small quantities by multi-step processes and sell at higher prices. The cost can be reduced by the use of low-cost residues, efficient catalysts, integration in biorefineries and the commercialization of co-products. Price premiums are more easily accepted in high-value sectors such as pharmaceuticals and cosmetics, where regulatory pressure and the cost of waste treatment are high, and these sectors are likely to lead early adoption.

Challenges and Future Perspectives:

Several technical challenges remain. Many bio-based solvents are highly polar and hydrophilic, which complicates their separation from water and increases the energy required for recovery. Some are unstable under acidic, basic or oxidizing conditions, which limits their use in certain reactions, and impurities from biomass can affect reproducibility. Scale-up from laboratory to industrial production often reveals problems in catalyst lifetime, product purification and process integration, which require engineering as well as chemical solutions.Future research will focus on the design of solvents that combine low toxicity, easy recovery and broad applicability, and computational tools are increasingly used to support this goal. Computer-aided molecular design, machine learning models that predict solubility and toxicity, and high-throughput screening can identify promising candidates much faster than trial-and-error experimentation. Mixtures of bio-based solvents, deep eutectic solvents based on natural compounds and neoteric systems such as supercritical carbon dioxide and water-based media are also expected to play a larger role.Successful adoption will depend on cooperation among academia, industry and policy makers. Investment in biorefinery infrastructure, standardized life cycle data, supportive regulation and training of chemists and engineers in green solvent selection are all required. For developing countries including Pakistan, the development of bio-based solvents from local agricultural residues offers an opportunity to reduce imports, create rural employment and move toward a circular bioeconomy, provided that research capacity and industrial partnerships are strengthened.



Summary:

Bio-based solvents derived from sugars, lignocellulosic residues, vegetable oils and other renewable resources provide a realistic route to more environmentally responsible chemical manufacturing. Alcohols, esters, ethers, lactones, terpenes and levoglucosenone derivatives can replace many hazardous petrochemical solvents in synthesis, extraction, coatings and materials processing. Their real benefit, however, depends on the feedstock, the efficiency of production and recovery, and complete evaluation of toxicity and life cycle impact. Technical limitations, higher costs and regulatory requirements are still significant barriers, but advances in catalysis, biorefinery integration and computational design are steadily reducing them. Continued research and collaboration will be necessary to make bio-based solvents a mainstream element of sustainable chemical industry.

References:

- Anastas, P. T., and Warner, J. C. (1998). Green Chemistry: Theory and Practice. Oxford University Press, Oxford.
- Clark, J. H., Farmer, T. J., Hunt, A. J., and Sherwood, J. (2015). Opportunities for bio-based solvents created as petrochemical and fuel products transition towards renewable resources. International Journal of Molecular Sciences, 16, 17101-17159.
- Gu, Y., and Jerome, F. (2013). Bio-based solvents: an emerging generation of fluids for the design of eco-efficient processes in catalysis and organic chemistry. Chemical Society Reviews, 42, 9550-9570.
- Capello, C., Fischer, U., and Hungerbuhler, K. (2007). What is a green solvent? A comprehensive framework for the environmental assessment of solvents. Green Chemistry, 9, 927-934.
- Prat, D., Wells, A., Hayler, J., Sneddon, H., McElroy, C. R., Abou-Shehada, S., and Dunn, P. J. (2016). CHEM21 selection guide of classical- and less classical-solvents. Green Chemistry, 18, 288-296.
- Camp, J. E. (2018). Bio-available solvent Cyrene: synthesis, derivatization, and applications. ChemSusChem, 11, 3048-3055.
- Pace, V., Hoyos, P., Castoldi, L., Dominguez de Maria, P., and Alcantara, A. R. (2012). 2-Methyltetrahydrofuran (2-MeTHF): a biomass-derived solvent with broad application in organic chemistry. ChemSusChem, 5, 1369-1379.
- Horvath, I. T., Mehdi, H., Fabos, V., Boda, L., and Mika, L. T. (2008). Gamma-valerolactone, a sustainable liquid for energy and carbon-based chemicals. Green Chemistry, 10, 238-242.
- Pereira, C. S. M., Silva, V. M. T. M., and Rodrigues, A. E. (2011). Ethyl lactate as a solvent: properties, applications and production processes, a review. Green Chemistry, 13, 2658-2671.

- Jessop, P. G. (2011). Searching for green solvents. Green Chemistry, 13, 1391-1398.
- Sheldon, R. A. (2005). Green solvents for sustainable organic synthesis: state of the art. Green Chemistry, 7, 267-278.
- Byrne, F. P., Jin, S., Paggiola, G., Petchey, T. H. M., Clark, J. H., Farmer, T. J., Hunt, A. J., McElroy, C. R., and Sherwood, J. (2016). Tools and techniques for solvent selection: green solvent selection guides. Sustainable Chemical Processes, 4, 7.