Open Horizon Scientific Review

Vol. 02 No.04 2024

Thermodynamic Modeling of Multicomponent Mixtures in Industrial Applications

Hassan Raza Qureshi

Department of Chemical Engineering, University of Engineering and Technology, Lahore, Pakistan

ABSTRACT

The design, optimization and safe operation of separation, reaction and transport processes in the chemical, petroleum, gas and energy industries rest on accurate descriptions of how multicomponent mixtures behave. Thermodynamic models translate molecular interactions into quantitative predictions of phase equilibria, densities, enthalpies and other properties needed by process simulators. This article reviews the principal approaches to modeling multicomponent mixtures, beginning with the thermodynamic criteria for equilibrium and proceeding through cubic equations of state, mixing rules, activity coefficient models, association-based equations such as SAFT and CPA, and electrolyte models. Methods for estimating parameters from experimental data and numerical algorithms for stability analysis and flash calculations are discussed, followed by industrial applications and selection guidelines. The review emphasizes that model choice should be guided by the chemical nature of the system, the pressure and temperature range and the quality of available data, and that extrapolation beyond the fitted domain demands careful validation.

Key words: *thermodynamic modeling, phase equilibrium, equation of state, activity coefficient, multicomponent mixtures*

Introduction:

Almost every industrial process handles mixtures rather than pure substances. Crude oil fractionation, natural gas processing, solvent extraction, distillation of alcohols, absorption of acid gases and crystallization of salts all depend on how components distribute among coexisting phases and how mixture properties vary with temperature, pressure and composition. Errors in thermodynamic predictions propagate directly into equipment sizing, energy consumption, product purity and safety margins, which makes the choice and calibration of a thermodynamic model one of the most consequential decisions in process engineering (Smith et al., 2005).

Two broad modeling philosophies have emerged. The first describes all phases with a single equation of state, a function relating pressure, volume and temperature that is extended to mixtures through mixing rules. The second treats the vapor phase with an equation of state or an ideal-gas approximation and describes the liquid phase through the excess Gibbs energy and activity

coefficients. Over the past decades these have been joined by models rooted in statistical mechanics that explicitly represent molecular association, chain length and electrostatic forces.

This article offers an organized overview of these approaches. It describes their theoretical basis, strengths and limitations, discusses how their parameters are obtained and how equilibrium calculations are performed, and concludes with their use in industrial practice and guidance for selecting an appropriate model.

1. Thermodynamic Foundations of Phase Equilibrium

Phase equilibrium in a multicomponent system is governed by the requirement that temperature, pressure and the chemical potential of each component be identical in all coexisting phases. Chemical potential cannot be measured directly, so it is expressed through fugacity, a quantity with units of pressure that acts as an effective partial pressure and equals the actual pressure for an ideal gas. Equality of fugacity of each component in every phase is therefore the working condition for equilibrium, and the ratio of vapor to liquid mole fractions, the equilibrium ratio, follows from it (Poling et al., 2001).

To reach practical expressions, fugacity is related to composition through either a fugacity coefficient, which measures deviation of a component in a phase from ideal-gas behavior, or an activity coefficient, which measures deviation of a liquid component from ideal solution behavior. A stable equilibrium state corresponds to the global minimum of the Gibbs energy of the system at fixed temperature and pressure, and this minimum principle underlies the stability tests used to decide how many phases are present. The Gibbs-Duhem relation additionally links the property changes of the components, imposing consistency on any proposed model and on experimental data.

2. Equations of State for Fluid Mixtures

Cubic equations of state are the workhorses of the hydrocarbon and gas industries because of their simplicity and reasonable accuracy. Building on the van der Waals concept, they separate pressure into a repulsive term, governed by a molecular volume parameter, and an attractive term, governed by an energy parameter that depends on temperature. The Soave modification of the Redlich-Kwong equation introduced a temperature-dependent attraction term tied to the acentric factor, markedly improving vapor pressure predictions (Soave, 1972). The Peng-Robinson equation altered the volume dependence of the attractive term and gave better liquid densities, and it remains one of the

most widely used models (Peng & Robinson, 1976).

These equations require only critical properties and acentric factors of the components, which are available for many substances, and they handle wide ranges of temperature and pressure including the near-critical region. Their weaknesses are also well known: liquid density predictions are often inaccurate unless volume translation is applied, and highly polar or associating fluids such as water, alcohols and amines are poorly represented without extensive adjustment. Virial equations and multiparameter reference equations offer higher accuracy for specific well-studied fluids and mixtures, but their complexity limits their use for general multicomponent systems (Poling et al., 2001).

3. Mixing Rules and Binary Interaction Parameters

Extending an equation of state from pure components to mixtures requires a rule for combining the parameters of each species. The classical van der Waals one-fluid mixing rules express the attraction parameter as a quadratic function of composition, with cross terms formed from the geometric mean of pure-component values corrected by a binary interaction parameter. The volume parameter is usually combined linearly. For mixtures of similar nonpolar molecules, such as light hydrocarbons, small interaction parameters of near zero provide good results, while mixtures involving carbon dioxide, hydrogen sulfide, nitrogen or polar compounds require parameters fitted to experimental data.

More flexible approaches make the interaction parameter depend on composition or temperature, or connect the equation of state to an activity coefficient model through the excess Gibbs energy at infinite or finite pressure. These so-called excess Gibbs energy mixing rules allow cubic equations to represent strongly nonideal mixtures while preserving their suitability at high pressure (Kontogeorgis & Folas, 2010). Care is required because adding parameters can improve the fit of binary data without improving the prediction of multicomponent behavior, and because some mixing rules violate the theoretically required quadratic composition dependence of the second virial coefficient.

4. Activity Coefficient Models for Nonideal Liquids

At low and moderate pressures, the liquid phase is conveniently described by the excess Gibbs energy, from which activity coefficients are derived. The simplest forms, such as the Margules and van Laar equations, are empirical expansions suitable for binary mixtures. Local composition models, beginning

with the Wilson equation, assume that the composition around a molecule differs from the bulk composition because of unequal intermolecular forces, and they represent a wide range of miscible systems with few parameters (Wilson, 1964). The nonrandom two-liquid model extended this idea to partially miscible systems and liquid-liquid equilibria (Renon & Prausnitz, 1968).

The universal quasichemical model, known as UNIQUAC, divides the excess Gibbs energy into a combinatorial part, reflecting molecular size and shape, and a residual part, reflecting energetic interactions (Abrams & Prausnitz, 1975). Its group contribution extension, UNIFAC, predicts activity coefficients from the functional groups present and is invaluable when no experimental data exist. As the figure below illustrates, a positive deviation from ideal solution behavior can raise the mixture pressure above that of both pure components and give rise to an azeotrope, a point at which vapor and liquid have the same composition and ordinary distillation cannot proceed further.

Activity coefficient models are valid mainly at pressures well below the critical region, since they treat the liquid as incompressible, and their parameters are typically temperature dependent. Their accuracy rests on the quality of binary data, and extrapolation to multicomponent mixtures relies on the assumption that only pairwise interactions are significant.

5. Advanced Association-Based Models: SAFT and CPA

Molecules such as water, alcohols, glycols, organic acids and amines form hydrogen bonds that strongly influence phase behavior, and traditional models describe them poorly. The statistical associating fluid theory, rooted in Wertheim's thermodynamic perturbation theory, builds a molecule from a chain of spherical segments with attractive sites that allow association. The Helmholtz energy is written as the sum of contributions from a reference fluid, chain formation, dispersion and association, and the first practical equation of this type appeared at the end of the 1980s (Chapman et al., 1990). Numerous variants have since been developed, including versions with polar terms and group contribution forms.

The cubic-plus-association equation takes a pragmatic route, combining a simple cubic equation for physical interactions with the association term from the statistical theory. It has proved particularly successful for systems containing water, glycols, methanol and hydrocarbons in oil and gas processing, such as hydrate inhibition and dehydration of natural gas (Kontogeorgis et al., 1996). These models require more pure-component

parameters than cubic equations and are computationally heavier, but they can often represent complex mixtures with temperature-independent interaction parameters and show better predictive capability over wide conditions.

6. Electrolyte and Aqueous Systems

Systems containing dissolved salts, acids and bases, such as brines, flue gas scrubbing solutions, fertilizer production streams and geothermal fluids, introduce long-range electrostatic interactions that cannot be handled by standard models. Electrolyte models add a term accounting for ionic interactions to a conventional description of short-range forces. The Debye-Huckel theory provides the limiting law for dilute solutions, and extensions with additional terms are applied at higher concentrations.

The electrolyte nonrandom two-liquid model combines a long-range Pitzer-Debye-Huckel contribution with a local composition term and has become a standard in process simulation for aqueous electrolyte systems (Chen & Evans, 1986). Other approaches use the Pitzer ion-interaction formulation, particularly for natural waters and salt solubility, or electrolyte equations of state based on association theory. Modeling must also address chemical equilibria, such as dissociation, complexation and precipitation, so that the speciation of the solution and the phase equilibria are solved simultaneously.

7. Parameter Estimation and Data Reconciliation

Every model is only as good as the parameters that feed it. Pure-component parameters are obtained from vapor pressure, saturated density and critical data, while binary interaction parameters are regressed from phase equilibrium measurements such as vapor-liquid, liquid-liquid and solid-liquid data. Regression minimizes an objective function that compares calculated and measured quantities, and the choice of objective, whether based on pressure, composition or equilibrium ratio deviations, influences the parameters obtained. Statistical tools such as confidence intervals and correlation analysis reveal whether parameters are well determined or interdependent.

Experimental data themselves contain errors, so thermodynamic consistency tests, based on the Gibbs-Duhem relation, are applied to detect unreliable measurements before regression. Large curated databases and open data compilations support this work. Overfitting is a persistent danger: a model with many adjustable parameters can reproduce a limited dataset while failing outside it, which is why validation against data not used in fitting and sensitivity analysis are

strongly recommended (Kontogeorgis & Folas, 2010).

8. Phase Equilibrium Algorithms and Flash Calculations


Turning a thermodynamic model into predictions requires robust numerical algorithms. The isothermal flash calculation determines the amount and composition of each phase at specified temperature, pressure and overall composition, and it is solved by combining material balances with equilibrium relations, typically through successive substitution followed by Newton-type acceleration. Bubble point and dew point calculations find the conditions at which the first bubble or drop of a new phase appears.A key difficulty is deciding how many phases exist and ensuring that the solution corresponds to the global minimum of the Gibbs energy. Stability analysis based on the tangent plane distance criterion tests whether a trial phase can lower the energy of the system and thereby detects hidden phases (Michelsen, 1982). Special attention is needed near critical points, where the algorithms become ill-conditioned, and for three-phase systems involving water, hydrocarbons and gas. Efficient and reliable solution procedures are crucial because flash calculations are repeated millions of times in dynamic simulation and optimization of large plants.

9. Industrial Applications and Process Simulation

Thermodynamic models are embedded in process simulators that engineers use daily. In oil and gas production, cubic equations and association models predict phase envelopes, hydrate formation, water content of gas and the behavior of reservoir fluids during depressurization. In refining and petrochemicals, they enable design of distillation columns, absorbers and extractors for hydrocarbon streams, while activity coefficient models govern solvent-based separations such as extractive and azeotropic distillation in the chemical and pharmaceutical industries.

In power generation and carbon capture, models of amine and carbonate solutions describe absorption of carbon dioxide, and in refrigeration and heat pump design, equations of state for refrigerant mixtures predict cycle performance. Electrolyte models support desalination, fertilizer manufacture and hydrometallurgy. Model selection generally follows the nature of the system: cubic equations for nonpolar mixtures at high pressure, activity coefficient models for polar liquids at low pressure, association equations for hydrogen-bonding systems over wide conditions and electrolyte models for ionic solutions. Whatever the choice, thorough validation against reliable data

in the operating range and documentation of model limits are essential for dependable design.



Summary

Thermodynamic modeling links molecular-level interactions to the macroscopic behavior of industrial mixtures. Equations of state, supported by suitable mixing rules, provide a unified description of fluids over wide pressure ranges, while activity coefficient models give accurate representation of nonideal liquids at moderate pressures. Association-based and electrolyte models extend predictive ability to hydrogen-bonding and ionic systems that challenge simpler formulations. Reliable results require careful parameter estimation, consistency testing of data and robust numerical algorithms for stability and flash calculations. Practical model selection should weigh chemical nature, operating range, data availability and computational demand, and should be confirmed by validation. Continued progress in molecular simulation, group contribution methods and data-driven techniques promises further gains in accuracy and predictive power.

References:

- Abrams, D. S., & Prausnitz, J. M. (1975). Statistical thermodynamics of liquid mixtures: a new expression for the excess Gibbs energy of partly or completely miscible systems. AIChE Journal, 21(1), 116–128.
- Chapman, W. G., Gubbins, K. E., Jackson, G., & Radosz, M. (1990). New reference equation of state for associating liquids. Industrial & Engineering Chemistry Research, 29(8), 1709–1721.
- Chen, C.-C., & Evans, L. B. (1986). A local composition model for the excess Gibbs energy of aqueous electrolyte systems. AIChE Journal, 32(3), 444–454.
- Kontogeorgis, G. M., & Folas, G. K. (2010). Thermodynamic Models for Industrial Applications: From Classical and Advanced Mixing Rules to Association Theories. Wiley.
- Kontogeorgis, G. M., Voutsas, E. C., Yakoumis, I. V., & Tassios, D. P. (1996). An equation of state for associating fluids. Industrial & Engineering Chemistry Research, 35(11), 4310–4318.

- Michelsen, M. L. (1982). The isothermal flash problem. Part I. Stability. Fluid Phase Equilibria, 9(1), 1–19.
- Peng, D.-Y., & Robinson, D. B. (1976). A new two-constant equation of state. Industrial & Engineering Chemistry Fundamentals, 15(1), 59–64.
- Poling, B. E., Prausnitz, J. M., & O'Connell, J. P. (2001). The Properties of Gases and Liquids (5th ed.). McGraw-Hill.
- Renon, H., & Prausnitz, J. M. (1968). Local compositions in thermodynamic excess functions for liquid mixtures. AIChE Journal, 14(1), 135–144.
- Smith, J. M., Van Ness, H. C., & Abbott, M. M. (2005). Introduction to Chemical Engineering Thermodynamics (7th ed.). McGraw-Hill.
- Soave, G. (1972). Equilibrium constants from a modified Redlich-Kwong equation of state. Chemical Engineering Science, 27(6), 1197–1203.
- Wilson, G. M. (1964). Vapor-liquid equilibrium. XI. A new expression for the excess free energy of mixing. Journal of the American Chemical Society, 86(2), 127–130.